

IN THE CLAIMS:

1. (Cancelled)

2. (Cancelled)

3. (Currently Amended) The method of claim ~~±~~29, further comprising the step of notifying the second user at the second terminal of the completed voice message prior to said step of ~~immediately~~-sending.

4. (Currently Amended) The method of claim 3, wherein said step of ~~immediately~~-sending the received voice message to the second terminal is carried out only after the second user signals acceptance.

5. (Currently Amended) The method of claim ~~±~~29, further comprising the steps of:
receiving a ~~completed~~-voice message from the second terminal spoken by the second user, and
~~immediately~~-sending the received voice message to the first terminal.

6. (Currently Amended) The method of claim 5, further comprising the step of checking the availability of said first terminal before carrying out said step of ~~immediately~~-sending the voice message ~~completed at~~ from the second terminal to the first terminal.

7. (Currently Amended) The method of claim ~~±~~29, further comprising the step of storing the ~~received~~ voice message

transmitted from the first terminal in the second terminal for playback by the second user at the convenience of the second user.

8. (Cancelled)

9. (Currently Amended) The apparatus of claim & 31, further comprising means for storing the voice message until the means for checking availability determines the second terminal is available.

10. (Currently Amended) The apparatus of claim & 31, further comprising means for notifying the second user at the second terminal of the received voice message from the first user prior to the received voice message transmission to the second terminal.

11. (Original) The apparatus of claim 10, wherein the received voice message is sent to the second terminal only after the second user signals acceptance.

12. (Currently Amended) The apparatus of claim & 31, further comprising:

means for receiving a voice message from the second terminal spoken by the second user in reply to the voice message from the first user; and

means for ~~immediately~~ sending the voice message received from the second user to the first terminal.

13. (Currently Amended) The apparatus of claim 12, further comprising means for checking the availability of the first

terminal before ~~immediately~~ sending the voice message received from the second terminal to the first terminal.

14. (Currently Amended) The apparatus of claim ~~8~~31, further comprising means for storing the voice message received in the second terminal for playback to the second user at the convenience of the second user.

15. (Cancelled)

16. (Currently Amended) The system of claim ~~15~~17, said service center further comprising means for notifying the second terminal of the voice message received from the first terminal wherein the received voice message from the first terminal is sent to the second terminal upon receiving an acceptance signal from the second terminal in response to the notification.

17. (Currently Amended) ~~The system of claim 15~~ A voice message system including a plurality of terminals and a voice message service center, said service center comprising:
means for receiving a voice message from a first user terminal;
means for storing the received voice message from the first terminal;

a presence service for checking availability of an intended second user at a second terminal; and

means for sending the stored received message from the first terminal to the second terminal if the second terminal is available, wherein one or more of said plurality of terminals comprises:

means for receiving said voice message at said first user terminal spoken by a first user for providing said voice message

from said first user terminal to said means for receiving said voice message at said service center;

means for storing voice messages including said voice message spoken by said first user;

means for receiving a designation signal from said first user designating a second user as an intended recipient;

means for retrieving the stored voice message in response to the designation signal for providing the voice message retrieved from storage and the designation signal; and

means for sending the voice message retrieved from storage and the designation signal to the second user of the voice message system as an outgoing voice message.

18. (Previously Presented) The voice message system of claim 17, wherein said one or more of said plurality of terminals further comprises:

means for receiving an incoming voice message from the second user for storage in the means for storing received voice messages; and

means for playback of the incoming voice message to the first user after retrieval from the means for storing voice messages by the means for retrieving stored voice messages.

19. (Original) The voice message system of claim 18, wherein said one or more of said plurality of terminals further comprises:

means for receiving notification of the incoming voice message from the second user for display or notification thereof to the first user; and

means responsive to an acceptance indication input signal from the first user for sending the acceptance indication input

signal for use in the voice message system in deciding whether to send the incoming voice message from the second user to the first user.

20. (Original) The voice message system of claim 17, wherein the means for receiving the voice message spoken by the first user includes voice recognition means for recognizing the voice message spoken by the first user for providing the voice message as a text message for storage in and retrieval from the means for storing voice messages as a text message for transmission as an outgoing text voice message via a short message service center.

21. (Original) The voice message system of claim 20, wherein the means for receiving an incoming voice message from the second user may include means for receiving an incoming text voice message for storage in the means for storing voice messages as a text message and wherein the means for playback of the incoming text voice message is for displaying the incoming text message on a display of the user equipment.

22. (Previously Presented) The system of claim 20, wherein the means for receiving an incoming voice message from the second user is means for receiving an incoming text voice message for storage in the means for storing voice messages as a text message and wherein the means for retrieving the stored voice message is also for converting the retrieved voice message to a voice signal for playback on a means for playback as an enunciated voice message.

23. (Original) User equipment for use in a voice message system, comprising:

means for receiving a short voice message (SVM) spoken by a first user;

means for storing SVMs including said SVM spoken by said first user;

means for receiving a designation signal from the first user designating a second user as an intended recipient;

means for retrieving the stored SVM in response to the designation signal for providing the SVM retrieved from storage and the designation signal; and

means for sending the SVM retrieved from storage and the designation signal to the second user of the voice message system as an outgoing SVM.

24. (Original) The user equipment of claim 23, further comprising:

means for receiving an incoming SVM from the second user for storage in the means for storing SVMs; and

means for playback of the incoming SVM to the first user after retrieval from the means for storing SVMs by the means for retrieving stored SVMs.

25. (Original) The user equipment of claim 24, further comprising:

means for receiving notification of the incoming SVM from the second user for display or notification thereof by the user equipment; and

means responsive to an acceptance indication input signal from the first user for sending the acceptance indication input signal for use in the voice message system in deciding whether to send the incoming SVM from the second user to the user equipment of the first user.

26. (Original) The user equipment of claim 23, wherein the means for receiving the SVM spoken by the first user is voice recognition means for providing the SVM as a text message for storage in and retrieval from said means for storing SVMs as a text message for transmission as an outgoing text SVM via a short message service (SMS) center.

27. (Previously Presented) The user equipment of claim 24, wherein the means for receiving an incoming SVM from the second user is means for receiving an incoming text SVM for storage in the means for storing SVMs as a text message and wherein the means for playback of the incoming text SVM is for displaying the incoming text message on a display of the user equipment.

28. (Cancelled)

29. (Currently Amended) ~~The method of claim 28~~ Method for use in a telecommunications network for providing messages between users, comprising

receiving a voice message transmitted from a first terminal for forwarding to a second user at a second terminal,

checking availability of said second terminal or said second user using a presence service, and sending the voice message only if available, wherein said checking availability is a checking of a status marker (298) of a presence tuple (292) among a plurality of presence tuples of presence information (290) maintained by a presence service (248), wherein said immediately sending the received voice message is carried out by a service (270, 310) sending the received voice message to an inbox (274) having an inbox address (314) associated with said presence tuple (292).

30. (Cancelled)

31. (Currently Amended) ~~The apparatus of claim 30~~ Apparatus for use in a telecommunications network for providing messages between users, comprising:

means for receiving a voice message from a first terminal spoken by a first user for a second user at a second terminal;

means for checking availability of said second terminal or said second user using a presence service; and

means for sending the received voice message to the second terminal if available, wherein said means for checking availability is carried out by a presence service (248) checking a status marker (298) of a presence tuple (292) among a plurality of presence tuples of presence information (290) maintained by a presence service (248), wherein said means for of immediately sending is carried out by a service (270, 310) sending the received voice message to an inbox (274) having an inbox address (314) associated with said presence tuple (292).

32. (Cancelled)

33. (Currently Amended) ~~The system of claim 32~~ A voice message system including a plurality of terminals and a voice message service center, said service center comprising:

means for receiving a voice message from a first user terminal;

means for storing the received voice message from the first terminal;

a presence service for checking availability of an intended second user at a second terminal; and

means for sending the stored received message from the first

terminal to the second terminal if the second terminal is available, wherein said presence service is for checking availability by checking a status marker (298) of a presence tuple (292) among a plurality of presence tuples of presence information (290) maintained by a presence service (248), wherein said means for ~~of immediately~~ sending is carried out by a service (270, 310) sending the received voice message to an inbox (274) having an inbox address (314) associated with said presence tuple (292).

34. (Previously Presented) The user equipment of claim 23, wherein said means for sending comprises an SVM sender user agent (280).

35. (Previously Presented) The user equipment of claim 24, wherein said means for receiving an incoming SVM is an SVM inbox user agent (282).

36. (Cancelled)

37. (Previously Presented) A messaging system comprising at least one terminal and a server, wherein

the terminal comprises means for transmitting presence information to the server and means for receiving presence information from the server, and the server comprises means for maintaining presence information characterized in that said presence information includes presence tuples, each tuple comprising a status marker and a communication address identifying at least one of a short voice message (SVM) service and an SVM inbox address, and in that

said system includes an SVM service, responsive to an

instant voice message from a sending principal addressed to an SVM inbox, for checking said status marker of said SVM inbox and for delivering said instant voice message if said status marker indicates availability for receipt thereof.

38. (Previously Presented) Terminal for accessing an instant messaging service for receiving instant messages from senders of instant messages and for providing instant messages to inboxes, said service associated with a presence service for receiving presence information about presentities and for providing said presence information to watchers, said terminal comprising:

a short voice message (SVM) watcher user agent (278) for receiving presence information about an SVM presentity (254); and

an SVM sender user agent (280) for providing an SVM to an SVM server (270) for delivery if said presence information indicates availability.

39. (Previously Presented) The terminal of claim 38, further comprising:

an SVM presence user agent (276) for interacting with said SVM presentity; and

an SVM inbox user agent (282) for interacting with an SVM inbox (274).

40. (Previously Presented) A data structure embodied in a computer-readable medium for storage in a physical device, characterized in that

the data structure is a short voice message (SVM) presence information (290) database for storing SVM presence tuples (292, 294, 296, ..., n), each tuple having a status marker (298) indicative of availability for receipt of short voice messages,

944-003.81-1
Serial No. 09/911,078

and a communication address (302, 304, ..., n) indicative of at least one of an SVM service (310, 312, ..., n) and an SVM inbox address (314, 316, ..., n).